



REMOTE 3104, 5104

AIRBORNE PARTICLE COUNTERS

Incorporating the latest in laser optical particle counting technology, Lighthouse designed the **REMOTE 3104** and **5104** for continuous trouble-free operation.

With a sensitivity of 0.3 and 0.5 micron, respectively, at a flow rate of 1.0 CFM (28.3 LPM), the **REMOTE 3104** and **5104** provide real-time continuous data collection at a cost-effective price per point.

Using an external vacuum source, the compact **REMOTE 3104** and **5104** provide versatile mounting options and can be installed where space is at a premium. The optional T/RH Probe can be mounted up to eight feet from the instrument by using an optional extension cable.

The **REMOTE 3104** and **5104** integrate seamlessly into large facility monitoring and management systems and transfer up to 4 channels of simultaneous particle count and environmental data using RS-485 Modbus.

With the optional Network or Wireless Adapter, the **REMOTE 3104** or **5104** can be connected to TCP/IP LANs.

**Designed and built by
Lighthouse - a name you can trust.**

Lighthouse is an ISO 9001:2008 Registered company.

www.golighthouse.com

Features:

- ★ REMOTE 3104: 0.3 -25 μ m
- ★ REMOTE 5104: 0.5 -25 μ m
- ★ 1.0 CFM (28.3 LPM) Flow Rate
- ★ Up to 4 Channels of Simultaneous Data
- ★ All Models Meet ISO 21501-4 Standards
- ★ Compact Size
- ★ Stainless Steel Enclosure
- ★ Status Indicators
- ★ External Alarm Connector
- ★ Optional Temperature/Relative Humidity Probe
- ★ RS-485 Modbus Output
- ★ Facility Monitoring Systems Interface
- ★ Versatile Mounting Options
- ★ External Vacuum Source
- ★ Designed for Reliability

Benefits:

- ★ 2 Year Warranty
- ★ Installs in Limited Space
- ★ Cost Effective Price per Point
- ★ Proven Data Integrity
- ★ Proven Reliability
- ★ Continuous Real-Time Data
- ★ Easy System Integration
- ★ International Support
- ★ Low Cost of Ownership




Optional T/RH
Probe



Direct Mount
Isokinetic
Probe



RJ45
Connector



Status LEDs



Alarm Relay



Flow Status
Monitoring



Specifications:

	3104	5104
Size Range:	0.3 - 25.0µm	0.5 - 25.0µm
Channel Sizes:	Standard: 0.3, 0.5µm Optional: 0.3, 0.5, 0.7, 1.0µm; 0.3, 0.5, 1.0, 5.0µm; Optional: 0.3, 0.5, 5.0, 10.0µm	Standard: 0.5, 5.0µm; 0.5, 10.0µm Optional: 0.5, 1.0, 5.0, 10.0µm; 0.5, 5.0, 10.0, 25.0µm
Counting Efficiency:	50% @ 0.3 µm; 100% for particles > 0.45 µm (per ISO 21501-4)	50% @ 0.5 µm; 100% for particles > 0.75 µm (per ISO 21501-4)

Additional channel sizes are available - please contact your Sales Engineer for information regarding these options.

Flow Rate:	1.0 CFM (28.3 LPM)
Laser Source:	Laser Diode
Zero Count Level:	<1 count / 5 minutes (per ISO 21501-4)
Concentration Limits:	500,000 Particles / ft ³ @ 5% Coincidence Loss
Calibration:	NIST Traceable
Data Storage:	Rotating Buffer, 2000 Records
Vacuum Requirements:	External Vacuum >18" (45.72) of Hg
Air Flow:	Internally Monitored
Communication Modes:	RS-485 MODBUS
LED Indicators:	Power, Flow, Service, Sampling
Connector:	RJ45
Supporting Software:	LMS XChange, Lighthouse Monitoring System, LMS Express, LMS Express RT, LMS Net
Environmental Sensors:	(Optional) Temperature/Relative Humidity Probe 32 - 122F (0-50C)+/-1F (0.5C), 0 - 100% RH +/-2%
External Alarm Output:	Normally Open Dry Contact Rated 0-60 V AC/DC 1 Amp
Enclosure:	Stainless Steel
Power:	24 VDC
Dimensions:	REMOTE 3104: 3.5"(l) x 4.2"(w) x 3.3"(h) [8.89 x 10.66 x 8.38 cm] REMOTE 5104: 1.7"(l) x 4.2"(w) x 3"(h) [4.3 x 10.7 x 7.6 cm]
Weight:	REMOTE 3104: 2 lb (0.90 kg); REMOTE 5104: 0.97 lb (0.44 kg)

Environmental Conditions:

Operating: 50°F to 104°F (10°C to 40°C) / 20% to 95% non-condensing
Storage: 14°F to 122°F (-10°C to 50°C) / Up to 98% non-condensing



Accessories:

Included:
 Operating Manual on CD

Optional:
 Printed Operating Manual; RS-485 Hub with Power Supply; RS-232 Communication Cable and Adapter; USB to Serial Port Converter; Network Adapter; Wireless Network Adapter; Isokinetic Sampling Probes; Vacuum Tubing; Sample Tubing; Data Cable; Purge Filter; Power Supply; Temperature/ Relative Humidity Probe; 8' T/RH Probe Extension Cable; REMOTE Mounting Kit; LMS XChange, LMS Express; Express RT, LMSNet software; RS-485 Communication Kit; High-Pressure Diffuser.

Manufactured by:

Distributed by:



SAMPLE SYSTEM INTEGRATION

laftech

Call: 1300 306 002 www.laftech.com.au

LAF Technologies Pty Ltd
 Head Office: 12 Royan Place, Bayswater North, VIC 3153 Australia



Accredited Laboratory