

ScanAir

Smart Upstream Sampling
and Downstream Filter Scanning

Lighthouse Worldwide Solutions Operations

Corporate Headquarters

47300 Kato Road
Fremont, CA 94538
USA

Tel: +1 510 438 0500
Fax: +1 510 438 3840

Manufacturing Operations

1221 Disk Drive
Medford, OR 97501
USA

Tel: +1 541 770 5905
Fax: +1 541 770 2033

Benelux Operations

Van Heemstraweg 19-A
6657 KD Boven-Leeuwen
The Netherlands

Tel: +31 487 560811
Fax: +31 487 560013

EMEA Operations

Mimar Sinan Mh. Cavusbasi Cd.
Ozge Sk. Zin D Business Center
NO: 1/26
Cekmekoy/Istanbul
Turkey

Tel: +90 216 640 0 597
Fax: +90 216 640 0 598

Thailand Operations

9/13 Moo 5, Phaholyothin Rd.
T. Klongneung, A. Klongluang
Pathumthani, 12120
Thailand

Tel: +662 902 2722-3
Fax: +662 902 2724

Malaysia Operations

No. 18-32-A1 & A2
Gurney Tower, Persiaran Gurney
Georgetown, 10250 Penang
Malaysia

Tel: +604 370 1229
Fax: +604 370 1209

DISTRIBUTED BY:

laftech

Call: 1300 306 002 www.laftech.com.au

LAF Technologies Pty Ltd
Head Office: 12 Royan Place, Bayswater North, VIC 3153 Australia



MADE IN USA

www.golighthouse.com

LIGHTHOUSE
WORLDWIDE SOLUTIONS

ScanAir

Smart Upstream Sampling
and Downstream Filter Scanning



LIGHTHOUSE
WORLDWIDE SOLUTIONS



ScanAirPro

Scans Filters for Leaks and Efficiency

THE new Lighthouse ScanAir Pro System is a particle counter based HEPA/ULPA filter scanning system. It is the only easy and lightweight method for testing PTFE HEPA filters. Use it to scan filter media for leaks. Incorporating an ergonomic lightweight scanning probe with touchscreen user interface, the ScanAir Pro System also includes a SOLAIR portable particle counter and a dual-port dilutor that can be remotely switched between measurements from the touch screen handle. The ScanAir Pro System allows you to take an upstream and downstream measurement that displays real time percent leak information on the integrated touch screen display.



Quick Connections



Remote Start/Stop



Programmable Mode



Adjustable Probe Head

Features

- Ergonomic and Lightweight
- Touchscreen User Interface
- Upstream and Downstream Mode of Measurement
- Automatic Calculation of Alarm Threshold
- Scans & Sizes Leakers
- Display Percentage Leak During Downstream Mode
- Display Upstream or Downstream Measurements

Benefits

- Only Option for Testing PTFE Media Filters
- Ability to Challenge Test Filters With a Much Lower Concentration Than with a Photometer
- Virtually No Coalesce of Aerosol
- Use PSL Instead of PAO for Filter Challenge Testing
- Multi Function System Allowing Instruments to be Utilized for Other Applications
- Cost-effective Method for Testing

Applications

- Testing HEPA Filters and PTFE Media Filters
- Scan Filter Media for Leaks
- Cleanroom Classification
- Provide a Measurement of Filter Efficiency
- Testing Pressurized Gas

Operating:
50°F to 104°F (10°C to 40°C) / 20% to 95% non-condensing

Storage:
14°F to 122°F (-10°C to 50°C) / Up to 98% non-condensing



ScanAirFilterProbe

Smart Upstream Sampling and Downstream Filter Scanning System

OUR Lighthouse Scan Air Pro along with our SOLAIR portable particle counter can be used as a portable contamination detection system throughout the cleanroom environment.

The Scan Air Filter Pro includes a remote start/stop button and 3 meter (10-foot) cable. The remote switch features hands-free operation of the particle counter enabling the user to efficiently sample in compliance with ISO 14644-1.

The on-board alarm buzzer and LED quickly notify the user if a count exceeds the alarm threshold, even when the Scan Air Pro is being used in a high noise environment.



Quick Connections



Remote Start/Stop



Programmable Mode



Adjustable Probe Head

Features

- Adjustable Scan Head
- 1.0 CFM (28.3 LPM) Flow Rate
- Remote Start/Stop Button
- Remote Power and Alarm LEDs
- Remote Audible and Visual Alarm
- Lightweight 7oz. Design
- Standard 3 Meter (10 foot) Cable (Optional 3 Meter Extension Cable Available)
- Easily Integrates with SOLAIR Airborne Particle Counters (REV E and Newer)
- Facilitates ISO 14644-1 Compliance Testing
- Includes Headphone Jack With Adjustable Volume
- Ideal for Using from Ladders, Scissor Lifts or in Hard-to-Reach Places

Benefits

- 2 Year Warranty
- Small Footprint
- International Support
- Low Cost of Ownership

Applications

- Filter Efficiency Testing
- Filter Leak Testing
- Cleanroom Monitoring
- Facility Certification

Operating:
50°F to 104°F (10°C to 40°C) / 20% to 95% non-condensing

Storage:
14°F to 122°F (-10°C to 50°C) / Up to 98% non-condensing